

Tapered roller bearing 359A-354A-JTEKT - 359A-354A-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/359a-354a-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|----------------|----------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | T | B | C | r ₁ | r ₂ | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 46.038 | 85.000 | 20.638 | 21.682 | 17.462 | 3.6 | 1.2 | 71.8 | 81.7 | 4 600 | 6 200 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|---------------------|---------------------|----------|--------------------|----------------|------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 359A | 354A | 15.5 | 57.0 | 51.0 | 77.0 | 80.0 | 3.6 | 1.2 | 0.31 | 1.96 | 1.08 | 0.323 | 0.160 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952427317 |
| Inside diameter | 46.038 mm |
| Outside diameter | 85 mm |
| Thickness | 20.638 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE