

## Tapered roller bearing 2984-2924-JTEKT - 2984-2924-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/2984-2924-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	d <sub>a</sub>	d <sub>b</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
46.038	85.000	25.400	25.608	20.638	3.6	1.2	80.0	106	4 600	6 100

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
2984	2924	18.9	58.0	52.0	76.0	80.0	3.6	1.2	0.35	1.73	0.95	0.389	0.220

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427331
Inside diameter	46.038 mm
Inside diameter	1 13/16" inch
Outside diameter	85 mm
Outside diameter	3.346" inch
Thickness	25.4 mm
Thickness	1" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE