

## Tapered roller bearing 45282-45220-JTEKT - 45282-45220-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/45282-45220-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub. Oil lub.		
47.625	104.775	30.162	30.968	22.812	3.6	3.2	126	165	3 700	4 900	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
45282	45220	22.2	64.0	59.0	93.0	99.0	3.6	3.2	0.33	1.80	0.99	0.940	0.345

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427409
Inside diameter	47.625 mm
Outside diameter	104.775 mm
Thickness	30.162 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE