

Tapered roller bearing HH506348-HH506310-JTEKT - HH506348-HH506310-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/hh506348-hh506310-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_2 min.	C_r	C_{10}	Grease lub.	Oil lub.
49.212	114.300	44.450	44.450	30.068	3.6	3.2	212	283	3 700	5 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
HH506348	HH506310	30.6	71.0	61.0	97.0	107.0	3.6	3.2	0.40	1.49	0.82	1.49	0.834

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427454
Inside diameter	49.212 mm
Outside diameter	114.3 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE