

Tapered roller bearing 366-362A-JTEKT - 366-362A-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/366-362a-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
50.000	88.900	20.638	22.225	16.913	2.4	1.2	74.3	87.3	4 400	5 800

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
366	362A	16.1	59.0	55.0	81.0	84.0	2.4	1.2	0.32	1.88	1.03	0.351	0.166

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427591
Inside diameter	50 mm
Outside diameter	88.9 mm
Thickness	20.638 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE