

Tapered roller bearing 3780-3732-JTEKT - 3780-3732-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/3780-3732-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b min.	C_r	C_{10}	Grease lub.	Oil lub.
47.625	98.425	30.162	30.302	22.812	3.6	3.2	103	137	4 200	5 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
3780	3732	22.2	64.0	58.0	84.0	90.0	3.6	3.2	0.34	1.77	0.97	0.547	0.433

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427737
Inside diameter	50.8 mm
Outside diameter	98.425 mm
Thickness	30.162 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE