

## Tapered roller bearing 59200-59412-JTEKT - 59200-59412-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/59200-59412-jtekt>

Single-row tapered roller bearings ————— **Koyo**  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	d <sub>a</sub>	d <sub>b</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
47.625	104.775	36.512	36.512	22.575	3.6	3.2	148	187	3 900	5 100

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
59200	59412	26.9	68.0	61.0	92.0	99.0	3.6	3.2	0.40	1.49	0.82	0.767	0.623

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427768
Inside diameter	50.8 mm
Outside diameter	104.775 mm
Thickness	36.512 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE