

Tapered roller bearing 39575-39520-JTEKT - 39575-39520-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/39575-39520-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub. Oil lub.		
50.800	112.712	30.162	30.162	23.812	3.6	3.2	147	207	3 300	4 500	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
39575	39520	23.3	68.0	61.0	101.0	107.0	3.6	3.2	0.34	1.77	0.97	1.13	0.355

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427799
Inside diameter	50.8 mm
Inside diameter	2" inch
Outside diameter	112.712 mm
Outside diameter	4 7/16" inch
Thickness	30.162 mm
Thickness	1 3/16" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE