

Tapered roller bearing 65200-65500-JTEKT - 65200-65500-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/65200-65500-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_2 max.	C_r	C_{10}	Grease lub.	Oil lub.
50.800	127.000	44.450	44.450	34.925	3.6	3.2	208	289	3 300	4 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
65200	65500	35.2	75.0	69.0	107.0	119.0	3.6	3.2	0.49	1.23	0.68	1.86	1.03

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427812
Inside diameter	50.8 mm
Outside diameter	127 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE