

Tapered roller bearing 66212R-66462-JTEKT - 66212R-66462-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/66212r-66462-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
53.975	117.475	33.338	31.750	23.812	3.6	3.2	129	152	3 500	4 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
66212R	66462	33.2	73.0	67.0	100.0	111.0	3.6	3.2	0.83	0.96	0.53	1.03	0.552

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427904
Inside diameter	53.975 mm
Outside diameter	117.475 mm
Thickness	33.338 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE