

## Tapered roller bearing 65212-65500-JTEKT - 65212-65500-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/65212-65500-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



| Boundary dimensions (mm) |         |        |        |        |                  |                  | Basic load ratings (kN) |          | Limiting speeds (min <sup>-1</sup> ) |          |
|--------------------------|---------|--------|--------|--------|------------------|------------------|-------------------------|----------|--------------------------------------|----------|
| $d$                      | $D$     | $T$    | $B$    | $C$    | $r_{\text{max}}$ | $r_{\text{min}}$ | $C_r$                   | $C_{10}$ | Grease lub.                          | Oil lub. |
| 53.975                   | 127.000 | 44.450 | 44.450 | 34.925 | 3.6              | 3.2              | 208                     | 269      | 3 300                                | 4 400    |

  

| Bearing No. |            | Load center (mm)<br>$a$ | Mounting dimensions (mm) |       |       |       |                  |                  | Constant<br>$e$ | Axial load factors |       | (Refer.) Mass (kg) |            |
|-------------|------------|-------------------------|--------------------------|-------|-------|-------|------------------|------------------|-----------------|--------------------|-------|--------------------|------------|
| Inner ring  | Outer ring |                         | $d_s$                    | $d_b$ | $D_s$ | $D_b$ | $r_{\text{max}}$ | $r_{\text{min}}$ |                 | $Y_1$              | $Y_2$ | Inner ring         | Outer ring |
| 65212       | 65500      | 35.2                    | 77.0                     | 71.0  | 107.0 | 119.0 | 3.6              | 3.2              | 0.49            | 1.23               | 0.68  | 1.78               | 1.02       |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952427959 |
| Inside diameter  | 53.975 mm     |
| Outside diameter | 127 mm        |
| Thickness        | 44.45 mm      |
| Packaging        | 1             |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE