

Tapered roller bearing 389-382A-JTEKT - 389-382A-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/389-382a-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|-------|-------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | d_a | d_b | C_r | C_{10} | Grease lub. | Oil lub. |
| 55.575 | 96.838 | 21.000 | 21.946 | 19.875 | 2.4 | 0.8 | 80.4 | 101 | 3 900 | 5 200 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|------------|------------|--------------------|-------|--------------------|------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| 389 | 382A | 17.4 | 65.0 | 61.0 | 89.0 | 92.0 | 2.4 | 0.8 | 0.35 | 1.69 | 0.93 | 0.452 | 0.177 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952428130 |
| Inside diameter | 55.575 mm |
| Outside diameter | 96.838 mm |
| Thickness | 21 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE