


Tapered roller bearing 397-394A-JTEKT - 397-394A-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/397-394a-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
60.000	110.000	22.000	21.986	12.824	0.8	1.2	86.4	116	3 400	4 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
397	394A	21.3	69.0	68.0	101.0	104.5	0.8	1.2	0.40	1.49	0.82	0.637	0.259

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428369
Inside diameter	60 mm
Outside diameter	110 mm
Thickness	22 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE