


Tapered roller bearing HM813841-HM813811-JTEKT - HM813841-HM813811-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/hm813841-hm813811-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.
60.325	127.000	36.512	36.512	29.988	3.6	1.6	166	235	3 000	4 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
HM813841	HM813811	32.9	80.0	73.0	113.0	121.0	3.6	1.6	0.50	1.20	0.66	1.60	0.622

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428383
Inside diameter	60.325 mm
Inside diameter	2 3/8" inch
Outside diameter	127 mm
Outside diameter	5" inch
Thickness	36.512 mm
Thickness	1 7/16" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE