

Tapered roller bearing 65237-65500-JTEKT - 65237-65500-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/65237-65500-jtekt>

Single-row tapered roller bearings inch series Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|----------------|----------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | T | B | C | d _a | d _b | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 60.325 | 127.000 | 44.450 | 44.450 | 34.925 | 3.6 | 3.2 | 208 | 269 | 3 300 | 4 400 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|---------------------|---------------------|--------------------|----------------|-------------------|------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 65237 | 65500 | 35.2 | 82.0 | 71.0 | 107.0 | 119.0 | 3.6 | 3.2 | 0.49 | 1.23 | 0.68 | 1.59 | 1.02 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952428406 |
| Inside diameter | 60.325 mm |
| Outside diameter | 127 mm |
| Thickness | 44.45 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE