


Tapered roller bearing 477-472-JTEKT - 477-472-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/477-472-jtekt>

Single-row tapered roller bearings Koyo
Inch series



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	r ₃	C _r	C ₁₀	Grease lub.	Oil lub.
63.500	120.000	29.794	29.007	24.237	0.8	2.0		118	161	3 200	4 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
477	472	25.7	73.0	72.0	108.0	113.0	0.8	2.0	0.38	1.56	0.86	0.967	0.493

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428475
Inside diameter	63.5 mm
Outside diameter	120 mm
Thickness	29.794 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE