

Tapered roller bearing 39586-39520-JTEKT - 39586-39520-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/39586-39520-jtekt>

Single-row tapered roller bearings Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub. Oil lub.		
64.986	112.712	30.162	30.904	22.812	2.4	3.2	147	207	3 300	4 500	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
39586	39520	23.3	76.0	72.0	101.0	107.0	2.4	3.2	0.34	1.77	0.97	0.845	0.355

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428536
Inside diameter	64.986 mm
Outside diameter	112.712 mm
Thickness	30.162 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE