

Tapered roller bearing

JH211749A-JH211710-JTEKT - JH211749A-JH211710-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/jh211749a-jh211710-jtekt>

Single-row tapered roller bearings
inch series Koyo



| Boundary dimensions (mm) | | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | |
|--------------------------|---------|--------|--------|--------|----------------|----------------|------------------------|-------------------------|----------------|--------------------------------------|-------------|----------|
| d | D | T | B | C | d _a | d _b | r _a max. | r _b max. | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 65.000 | 120.000 | 39.000 | 38.500 | 32.000 | 7.1 | 2.8 | | | 189 | 255 | 3 200 | 4 300 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | Mass (kg) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|------------------------|------------------------|----------|--------------------|----------------|------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| JH211749A | JH211710 | 27.9 | 88.0 | 74.0 | 107.0 | 114.0 | 7.1 | 2.8 | 0.34 | 1.78 | 0.98 | 1.27 | 0.618 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952428567 |
| Inside diameter | 65 mm |
| Outside diameter | 120 mm |
| Thickness | 39 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE