

# Tapered roller bearing

## HM212049-HM212010-JTEKT - HM212049-HM212010-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/hm212049-hm212010-jtekt>

Single-row tapered roller bearings Koyo  
 inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.	
66.675	122.238	38.100	38.364	22.718	3.6	1.6	191	249	3 200	4 300	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
HM212049	HM212010	27.3	82.0	75.5	110.0	116.0	3.6	1.6	0.34	1.78	0.98	1.26	0.596

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428635
Inside diameter	66.675 mm
Outside diameter	122.238 mm
Thickness	38.1 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE