

Tapered roller bearing 6460-6420-JTEKT - 6460-6420-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/6460-6420-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
73.025	149.225	53.975	54.228	44.460	3.6	3.2	285	404	2 700	3 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
6460	6420	39.3	93.0	87.0	129.0	141.0	3.6	3.2	0.36	1.66	0.91	2.79	1.61

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428970
Inside diameter	73.025 mm
Outside diameter	149.225 mm
Thickness	53.975 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE