


Tapered roller bearing 744R-742-JTEKT - 744R-742-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/744r-742-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
73.025	150.089	44.450	46.672	38.612	3.6	3.2	264	368	2 500	3 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
744R	742	32.4	91.0	85.0	134.0	142.0	3.6	3.2	0.33	1.84	1.01	2.66	1.07

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428987
Inside diameter	73.025 mm
Inside diameter	2 7/8" inch
Outside diameter	150.089 mm
Outside diameter	5.909" inch
Thickness	44.45 mm
Thickness	1 3/4" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE