


Tapered roller bearing 762-752-JTEKT - 762-752-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/762-752-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.
73.025	161.925	47.625	48.260	38.100	3.6	3.2	273	391	2 400	3 200

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.		<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
762	752	35.5	92.0	97.0	144.0	150.0	3.6	3.2	0.34	1.76	0.97	3.18	1.61

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428994
Inside diameter	73.025 mm
Inside diameter	2 7/8" inch
Outside diameter	161.925 mm
Outside diameter	6 3/8" inch
Thickness	47.625 mm
Thickness	1 7/8" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE