

# Tapered roller bearing

## JLM714149-JLM714110-JTEKT - JLM714149-JLM714110-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/jlm714149-jlm714110-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
75.000	115.000	25.000	25.000	19.000	3.0	2.8	101	151	3 100	4 200

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
JLM714149	JLM714110	25.5	87.0	81.0	104.0	110.0	3.0	2.8	0.46	1.31	0.72	0.612	0.269

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429038
Inside diameter	75 mm
Inside diameter	2.953" inch
Outside diameter	115 mm
Outside diameter	4.528" inch
Thickness	25 mm
Thickness	0.984" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE