

Tapered roller bearing 495AX-492A-JTEKT - 495AX-492A-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/495ax-492a-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	d _a	d _b	C _r	C ₁₀	Grease lub.	Oil lub.
76.200	133.350	30.162	29.769	22.225	6.4	3.2	133	198	2 700	3 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
495AX	492A	29.8	98.0	86.0	120.0	128.0	6.4	3.2	0.44	1.35	0.74	1.20	0.430

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250134241
Inside diameter	76.2 mm
Outside diameter	133.35 mm
Thickness	30.162 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE