

Tapered roller bearing 756A-752-JTEKT - 756A-752-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/756a-752-jtekt>

Single-row tapered roller bearings
inch series

Koyo

100mm series

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{1 max}	<i>r</i> _{1 min}	<i>C</i> ₀	<i>C</i> ₁₀	Grease lub.	Oil lub.
79.375	161.925	47.625	48.260	38.100	7.9	3.2	273	391	2 400	3 200

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factor		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _{a max}	<i>r</i> _{a min}		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
756A	752	35.5	106.0	91.0	144.0	150.0	7.9	3.2	0.34	1.76	0.97	2.95	1.59

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429267
Inside diameter	79.375 mm
Outside diameter	161.925 mm
Thickness	47.625 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE