

Tapered roller bearing 27691-27620-JTEKT - 27691-27620-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/27691-27620-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.	
83.345	125.412	25.400	25.400	19.845	6.4	1.6	101	182	2 900	3 800	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
27691	27620	24.7	102.0	90.0	115.0	120.0	6.4	1.6	0.42	1.44	0.79	0.646	0.344

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429441
Inside diameter	83.345 mm
Inside diameter	3.281" inch
Outside diameter	125.412 mm
Outside diameter	4 15/16" inch
Thickness	25.4 mm
Thickness	1" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE