

Tapered roller bearing 749SR-742-JTEKT - 749SR-742-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/749sr-742-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
85.026	150.089	44.450	46.672	38.512	5.2	3.2	264	368	2 500	3 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
749SR	742	32.4	104.0	95.0	134.0	142.0	5.2	3.2	0.33	1.84	1.01	2.08	1.06

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429502
Inside diameter	85.026 mm
Outside diameter	150.089 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE