

Tapered roller bearing 766-752-JTEKT - 766-752-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/766-752-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min ⁻¹)		
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
88.900	161.925	47.625	48.260	32.100	7.1	3.2	273	391	2 400	3 200

Bearing No.		Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		d_a	d_b	D_a	D_b	r_a max.	r_b max.		Y_1	Y_2	Inner ring	Outer ring
766	752	35.5	113.0	99.0	144.0	150.0	7.1	3.2	0.34	1.76	0.97	2.48	1.59

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429601
Inside diameter	88.9 mm
Inside diameter	3 1/2" inch
Outside diameter	161.925 mm
Outside diameter	6 3/8" inch
Thickness	47.625 mm
Thickness	1 7/8" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE