

Tapered roller bearing L319249-L319210-JTEKT - L319249-L319210-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/l319249-l319210-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
95.250	130.175	20.638	21.432	16.670	1.6	1.6	97.0	187	2 600	3 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to Mass (kg))		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
L319249	L319210	22.2	107.0	101.0	122.0	125.0	1.6	1.6	0.35	1.72	0.95	0.548	0.248

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429809
Inside diameter	95.25 mm
Outside diameter	130.175 mm
Thickness	20.638 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE