

Tapered roller bearing 52375-52618-JTEKT - 52375-52618-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/52375-52618-jtekt>

Single-row tapered roller bearings
inch series

Koyo

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{1 max.}	<i>r</i> _{2 max.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
95.250	157.162	36.512	36.116	26.185	3.6	3.2	180	288	2 300	3 000

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _s	<i>d</i> _b	<i>D</i> _s	<i>D</i> _b	<i>r</i> _{s max.}	<i>r</i> _{b max.}		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
52375	52618	36.0	112.0	105.0	142.0	152.0	3.6	3.2	0.47	1.26	0.69	1.94	0.694

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429830
Inside diameter	95.25 mm
Outside diameter	157.162 mm
Thickness	36.512 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE