

Tapered roller bearing 52393-52618-JTEKT - 52393-52618-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/52393-52618-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	d_a	d_b	$r_{a/b}$	C_r	C_{10}	Grease lub.	Oil lub.
100.012	157.162	36.512	36.116	26.185	3.6	3.2		180	288	2 300	3 000

Bearing No.		Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring		d_a	d_b	D_a	D_b	r_a max.	r_b max.		Y_1	Y_2	Inner ring	Outer ring
52393	52618	36.0	113.0	115.0	142.0	150.0	3.6	3.2	0.47	1.26	0.69	1.74	0.694

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429946
Inside diameter	100.012 mm
Outside diameter	157.162 mm
Thickness	36.512 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE