

Tapered roller bearing L521949R-L521910-JTEKT - L521949R-L521910-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/l521949r-l521910-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min ⁻¹)		
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a max.	<i>r</i> _b max.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
107.950	146.050	21.432	21.432	106.670	1.6	1.6	86.4	187	2 300	3 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
L521949R	L521910	26.2	116.0	114.0	136.0	141.0	1.6	1.6	0.39	1.53	0.84	0.665	0.325

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430065
Inside diameter	107.95 mm
Outside diameter	146.05 mm
Thickness	21.432 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE