

# Tapered roller bearing

## L521949R-L521910-JTEKT - L521949R-L521910-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/l521949r-l521910-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub. Oil lub.		
107.950	146.050	21.432	21.432	10.670	1.6	1.6	86.4	187	2 300	3 100	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
L521949R	L521910	26.2	116.0	114.0	136.0	141.0	1.6	1.6	0.39	1.53	0.84	0.665	0.325

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430065
Inside diameter	107.95 mm
Outside diameter	146.05 mm
Thickness	21.432 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE