

Tapered roller bearing 64433R-64700-JTEKT - 64433R-64700-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/64433r-64700-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	r ₃	C _r	C ₁₀	Grease lub.	Oil lub.
109.992	177.800	41.275	41.275	30.162	3.6	3.2		234	380	2 000	2 700

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
64433R	64700	42.8	128.0	121.0	160.0	172.6	3.6	3.2	0.52	1.16	0.64	2.69	1.10

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430188
Inside diameter	109.992 mm
Inside diameter	4.33" inch
Outside diameter	177.8 mm
Outside diameter	7" inch
Thickness	41.275 mm
Thickness	1 5/8" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE