


Tapered roller bearing

JHM522649-JHM522610-JTEKT - JHM522649-JHM522610-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/jhm522649-jhm522610-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|-------------------------------|-------------------------------|-------------------------|------------------------|-------------|--------------------------------------|--|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _a max. | <i>r</i> _b max. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. | |
| 110.000 | 180.000 | 47.000 | 46.000 | 38.000 | 3.0 | 2.5 | 306 | 487 | 2 000 | 2 700 | |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|-------------------------------|----------|-----------------------|-----------------------|-------------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| JHM522649 | JHM522610 | 40.6 | 121.0 | 125.0 | 160.0 | 171.0 | 3.0 | 2.5 | 0.41 | 1.48 | 0.81 | 3.08 | 1.49 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952430256 |
| Inside diameter | 110 mm |
| Inside diameter | 4.331" inch |
| Outside diameter | 180 mm |
| Outside diameter | 7.087" inch |
| Thickness | 47 mm |
| Thickness | 1.85" inch |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE