


Tapered roller bearing

L540049-L540010-JTEKT - L540049-L540010-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/l540049-l540010-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	$r_{1\max}$	$r_{2\max}$	C_r	C_{10}	Grease lub.	Oil lub.
196.850	254.000	28.575	27.783	21.433	1.6	1.6	188	387	1 200	1 600

Bearing No.		Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring		d_s	d_b	D_s	D_b	$r_{s\max}$	$r_{b\max}$		Y_1	Y_2	Inner ring	Outer ring
L540049	L540010	43.1	206.0	214.0	238.0	243.0	1.6	1.6	0.40	1.51	0.83	2.34	1.02

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952431772
Inside diameter	196.85 mm
Outside diameter	254 mm
Thickness	28.575 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE