

Tapered roller bearing LM245833-LM245810-JTEKT - LM245833-LM245810-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/lm245833-lm245810-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.	
220.878	317.500	47.625	52.388	36.613	3.2	3.2	488	928	970	1 300	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
LM245833	LM245810	50.5	234.0	253.0	296.0	304.0	3.2	3.2	0.33	1.80	0.99	9.56	2.78

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952431796
Inside diameter	220.878 mm
Outside diameter	317.5 mm
Thickness	47.625 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE