

## Needle roller bearing BHTM916-JTEKT - BHTM916-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bhtm916-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
9	16	16	13.3	7.95	7.90	32 000	<b>BHTM916</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	8.991	9.000	15.977	15.995	12	13

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952469485
Inside diameter	9 mm
Outside diameter	16 mm
Thickness	16 mm
Weight	12 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE