

Needle roller bearing BHTM1020-JTEKT - BHTM1020-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bhtm1020-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|----------|-------------------------|----------|--------------------------------------|---|
| F_w | D | C | b min. | C_r | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 10 | 17 | 20 | 17.3 | 10.7 | 12.5 | 30 000 | BHTM1020 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 9.991 | 10.000 | 16.977 | 16.995 | 16 | 18 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952469621 |
| Inside diameter | 10 mm |
| Outside diameter | 17 mm |
| Thickness | 20 mm |
| Weight | 16 g |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE