

## Needle roller bearing BHTM1220-JTEKT - BHTM1220-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bhtm1220-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) |     |     |             | Basic load ratings (kN) |          | Limiting speeds (min <sup>-1</sup> ) |          | Bearing No. <sup>2)</sup> |                 |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|----------|---------------------------|-----------------|
| $F_w$                    | $D$ | $C$ | $b$<br>min. | $C_0$                   | $C_{10}$ | Oil lub.                             | Oil lub. | Caged type                |                 |
|                          |     |     |             |                         |          |                                      |          | With open ends            | With closed end |
| 12                       | 19  | 20  | 17.3        | 12.1                    | 14.9     | 26 000                               |          | <b>BHTM1220</b>           |                 |

| Full complement type |                 | Recommended dimensions (mm) |        |                                |        | (Refer.) Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends       | With closed end | Shaft dia. (H6)<br>min.     | max.   | Housing bore dia. (N7)<br>min. | max.   | With open ends    | With closed end |
| —                    | —               | 11.989                      | 12.000 | 18.972                         | 18.993 | 17                | 19              |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952469782 |
| Inside diameter  | 12 mm         |
| Inside diameter  | 0.472" inch   |
| Outside diameter | 19 mm         |
| Outside diameter | 0.748" inch   |
| Thickness        | 20 mm         |
| Thickness        | 0.787" inch   |
| Weight           | 17 g          |
| Packaging        | 1             |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE