

## Needle roller bearing BHTM1225-JTEKT - BHTM1225-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bhtm1225-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Caged type	
							With open ends	With closed end
12	19	25	—	15.0	19.6	26 000	<b>BHTM1225</b>	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	11.989	12.000	18.972	18.993	21	—

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952469805
Inside diameter	12 mm
Outside diameter	19 mm
Thickness	25 mm
Weight	21 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE