

Needle roller bearing 14BTM2016-JTEKT - 14BTM2016-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/14btm2016-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|----------|-------------------------|----------|--------------------------------------|------------------|---------------------------|--|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type | | |
| | | | | | | With open ends | | With closed end | |
| 14 | 20 | 16 | 13.3 | 8.75 | 11.4 | 25 000 | 14BTM2016 | | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 13.989 | 14.000 | 19.972 | 19.993 | 13 | 15 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952469980 |
| Inside diameter | 14 mm |
| Outside diameter | 20 mm |
| Thickness | 16 mm |
| Weight | 13 g |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE