

Needle roller bearing BHTM1525-JTEKT - BHTM1525-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bhtm1525-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F _w	D	C	b min.	C ₀	C ₁₀	Oil lub.	Caged type With open ends With closed end
15	22	25	—	17.7	25.0	23 000	BHTM1525

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	14.989	15.000	21.972	21.993	26	—

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952470252
Inside diameter	15 mm
Inside diameter	0.591" inch
Outside diameter	22 mm
Outside diameter	0.866" inch
Thickness	25 mm
Thickness	0.984" inch
Weight	26 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE