

Needle roller bearing MKM162414U-JTEKT - MKM162414U-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/mkm162414u-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾		
F_w	D	C	b min.	C_0	C_{10}	Oil lub.	Caged type		
								With open ends	With closed end
16	24.15	14	12.6	8.45	9.05	12 000 ¹⁾	MKM162414U		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	24.122	24.143	—	19

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952470382
Inside diameter	16 mm
Outside diameter	24.15 mm
Thickness	14 mm
Weight	19 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE