

## Needle roller bearing BTM1710-JTEKT - BTM1710-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/btm1710-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>		
F <sub>w</sub>	D	C	b min.	C <sub>10</sub>	C <sub>90</sub>	Oil lub.	Caged type		
								With open ends	With closed end
17	22	10	—	5.05	6.90	21 000	<b>BTM1710</b>		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	16.989	17.000	21.972	21.993	8.2	—

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952470412
Inside diameter	17 mm
Outside diameter	22 mm
Thickness	10 mm
Weight	8.2 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE