


## Needle roller bearing BTM2212-JTEKT - BTM2212-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/btm2212-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>0</sub>	C <sub>0r</sub>	Oil lub.	Caged type	
						With open ends		With closed end
22	29	12	—	9.92	13.0	16 000	<b>BTM2212</b>	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (F6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	28.972	28.993	19	—

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471181
Inside diameter	22 mm
Outside diameter	29 mm
Thickness	12 mm
Weight	19 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE