

Needle roller bearing 22BTM3018-JTEKT - 22BTM3018-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/22btm3018-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|----------|---------------------------|-----------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 22 | 30 | 18 | — | 16.7 | 24.5 | 16 000 | 22BTM3018 | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 21.987 | 22.000 | 29.972 | 29.993 | 31 | — |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952471242 |
| Inside diameter | 22 mm |
| Outside diameter | 30 mm |
| Thickness | 18 mm |
| Weight | 31 g |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE