

Needle roller bearing MKM4030-JTEKT - MKM4030-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/mkm4030-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_r	C_{0r}	Oil lub.	Caged type With open ends With closed end
40	50	30	27.3	43.0	82.5	9 100	MKM4030

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	39.984	40.000	49.967	49.992	109	123

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952472645
Inside diameter	40 mm
Inside diameter	1.575" inch
Outside diameter	50 mm
Outside diameter	1.969" inch
Thickness	30 mm
Thickness	1.181" inch
Weight	123 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE