

## Needle roller bearing MKM5030-JTEKT - MKM5030-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/mkm5030-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	Oil lub.	Caged type With open ends    With closed end	
50	62	30	27.3	52.8	98.5	7 300	MKM5030

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	49.984	50.000	61.961	61.991	153	173

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952472980
Inside diameter	50 mm
Outside diameter	62 mm
Thickness	30 mm
Weight	173 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE