


## Roller bearing NN3016K-JTEKT - NN3016K-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/nn3016k-jtekt>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>a</sub></i>	<i>C</i>	<i>C<sub>02</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
80	125	34	1.1	—	113	119	166	4 800	5 800	—	—
				Mounting dimensions (mm)					(Refer.) Mass (kg)		
Cylindrical bore		Tapered bore		<i>d<sub>a</sub></i> min.	<i>d<sub>a</sub></i> max.	<i>D<sub>a</sub></i> min.	<i>D<sub>a</sub></i> max.	<i>r<sub>a</sub></i> min.	<i>r<sub>a</sub></i> max.	Cylindrical bore	Tapered bore
				86.5	—	118.5	114	1	—	1.55	1.50

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473758
Inside diameter	80 mm
Outside diameter	125 mm
Thickness	34 mm
Weight	1500 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE